



RTSP



KW COMPANY profile

KW standard

K-KLAD, coating system

OUR commitment

Terms and Conditions

Warranty

ONLINE CATALOG

Contact Us

Round Tapered Steel Poles

Pole Shaft

The pole shaft is one or two section design, each section being fabricated from standard 11 gauge (0.1196"), 7 gauge (0.1793"), or 3 gauge (0.2391") steel. The pole shaft material is a weldable grade hot rolled commercial quality carbon steel with a guaranteed minimum yield strength of 55,000 psi after fabrication. Each section is one-piece construction with a full length longitudinal weld and is cylindrical in cross-section having a uniform taper of 0.14 inches of diameter change per foot of length.

Base Plate

The anchor base is fabricated from structural quality hot rolled carbon steel plate that meets or exceeds a minimum yield strength of 36,000 psi. The anchor base telescopes the pole shaft and is circumferentially welded top and bottom. All welds are performed in accordance with the American Welding Society specification AWS D1.1, latest edition.

Anchor Bolts

Anchor bolts are fabricated from commercial quality hot rolled carbon steel bar that meets or exceeds a minimum yield strength of 55,000 psi. Four properly sized anchor bolts, each with two regular hex nuts and washers, are furnished and shipped with all poles unless otherwise specified. Anchor bolts shall have the threaded end galvanized a minimum of 8 inches in accordance with ASTM A153. Fully galvanized anchor bolts are available upon request.

Handhole

An oval reinforced gasketed handhole, having a nominal 3" x 5" or 4" x 6-1/2" inside opening, located 1'-6" above base, is standard on all poles. Optional 5" x 8" and 4" x 10" handholes are available (see options). A grounding provision is located inside the handhole ring.

Finishes

The **Standard Finish** is a polyester thermosetting powder coating applied to the surface of the substrate to a minimum of 3 mils for all color finishes. **Hot dip Galvanized** finish to a ASTM A123 specification or primed finish is also available. For optional finishes, see **K-KLAD** and **K-KLAD Over Galvanizing**.

HOW TO ORDER

When ordering KW lighting standards, mounting adaptors and accessories, be sure to specify the complete catalog number. Our catalog numbers reflect the precise specifications of the item ordered to ensure our customers will receive the product which meets their exact requirements.

The following explanation of the catalog numbers will be helpful in placing orders:



HIDE ALL CATALOG ITEMS



Catalog Number	Nominal Height	Pole Shaft	Gauge	Handhole Size	Anchor Bolt	Bolt Circle	80 MPH	90 MPH	100 MPH	Ship WT.	Select
RTSP10-4.5-11	10	4.5 x 3.1 x 10.0	11	3 x 5.0	0.75 x 17 x 3	8	45.6	37.2	30.7	72	Configure
RTSP12-4.8-11	12	4.8 x 3.1 x 12.0	11	3 x 5.0	0.75 x 17 x 3	8	42.3	34.6	28.6	84	Configure
RTSP14-5.1-11	14	5.1 x 3.1 x 14.0	11	3 x 5.0	0.75 x 17 x 3	8	40	32.7	27	96	Configure
RTSP15-5.4-11	15	5.4 x 3.3 x 15.0	11	3 x 5.0	0.75 x 17 x 3	8	33.5	27	22	104	Configure
RTSP16-5.4-11	16	5.4 x 3.1 x 16.0	11	3 x 5.0	0.75 x 17 x 3	8	32.3	26.3	21.6	109	Configure
RTSP18-5.6-11	18	5.6 x 3.1 x 18.0	11	3 x 5.0	0.75 x 17 x 3	8	28.6	23.1	18.9	122	Configure
RTSP20-5.9-11	20	6.1 x 3.3 x 20.0	11	3 x 5.0	0.75 x 30 x 3	9.5	22.7	18.1	14.6	149	Configure
RTSP20-6.1-11	20	6.1 x 3.3 x 20.0	11	3 x 5.0	0.75 x 30 x 3	9.5	22.7	18.1	14.6	173	Configure
RTSP20-6.5-11	20	6.5 x 3.7 x 20.0	11	4 x 6.5	1.00 x 36 x 4	9.5	42	34	27	188	Configure
RTSP25-6.1-11	25	6.1 x 2.6 x 25.0	11	3 x 5.0	0.75 x 30 x 3	9.5	16.7	13.3	10.6	173	Configure
RTSP25-6.6-11	25	6.8 x 3.3 x 25.0	11	4 x 6.5	0.75 x 30 x 3	10	18.9	14.8	11.6	190	Configure
RTSP25-6.8-11	25	6.8 x 3.3 x 25.0	11	4 x 6.5	0.75 x 30 x 3	10	27	21	15	213	Configure
RTSP25-7.0-11	25	6.8 x 3.3 x 25.0	11	4 x 6.5	1.00 x 36 x 4	10	35	24.6	20	230	Configure
RTSP25-7.5-11	25	7.5 x 4.0 x 25.0	11	4 x 6.5	1.00 x 36 x 4	10.5	42	32	26	253	Configure
RTSP30-6.8-11	30	6.8 x 2.6 x 30.0	11	4 x 6.5	0.75 x 30 x 3	10	14	10.8	8.3	213	Configure
RTSP30-7.5-11	30	7.5 x 3.3 x 30.0	11	4 x 6.5	1.00 x 36 x 4	10.5	22.1	17.5	13.9	265	Configure
RTSP30-8.0-11	30	8.1 x 3.9 x 30.0	11	4 x 6.5	1.00 x 36 x 4	11	24.8	19.4	15.3	293	Configure
RTSP30-8.5-11	30	8.5 x 4.3 x 30.0	11	4 x 6.5	1.00 x 36 x 4	11.5	29.1	22.8	18	309	Configure
RTSP30-9.0-11	30	9.0 x 4.8 x 30.0	11	4 x 6.5	1.00 x 36 x 4	12.5	32.5	25.5	20.1	331	Configure
RTSP30-9.0-7	30	9.0 x 4.8 x 30.0	7	4 x 6.5	1.25 x 42 x 6	12.5	54.5	43.6	35.3	493	Configure

RTSP30-10.0-11	30	10.0 x 5.8 x 30.0	11	4 x 6.5	1.00 x 36 x 4	13.5	41	31.5	24	388	Configure
RTSP30-11.0-7	30	11.0 x 6.8 x 30.0	7	4 x 6.5	1.25 x 42 x 6	15	62	47	37	720	Configure
RTSP35-7.5-11	35	7.5 x 2.6 x 35.0	11	4 x 6.5	1.00 x 36 x 4	10.5	15.7	12.3	9.7	283	Configure
RTSP35-8.0-11	35	8.1 x 3.2 x 35.0	11	4 x 6.5	1.00 x 36 x 4	11	17.3	13.4	10.4	311	Configure
RTSP35-8.5-11	35	8.5 x 3.6 x 35.0	11	4 x 6.5	1.00 x 36 x 4	11.5	21.8	16.9	13.1	338	Configure
RTSP35-9.0-11	35	9.0 x 4.1 x 35.0	11	4 x 6.5	1.00 x 36 x 4	12.5	24.6	19	14.7	358	Configure
RTSP35-9.0-7	35	9.0 x 4.1 x 35.0	7	4 x 6.5	1.25 x 42 x 6	12.5	42.3	33.7	27.1	534	Configure
RTSP35-10.0-11	35	10.0 x 4.5 x 35.0	11	4 x 6.5	1.00 x 36 x 4	13.5	31	23	17	480	Configure
RTSP35-11.0-7	35	11.0 x 6.1 x 35.0	7	4 x 6.5	1.25 x 42 x 6	15	62	47	37	720	Configure
RTSP39-8.1-11	39	8.1 x 2.6 x 39.0	11	4 x 6.5	1.00 x 36 x 4	11	13.7	10.5	8	327	Configure
RTSP39-9.0-11	39	9.0 x 3.5 x 39.0	11	4 x 6.5	1.00 x 36 x 4	12.5	19.6	14.9	11.2	376	Configure
RTSP39-9.0-7	39	9.0 x 3.5 x 39.0	7	4 x 6.5	1.25 x 42 x 6	12.5	37.5	29	22.5	597	Configure
RTSP39-10.0-11	39	10.0 x 4.5 x 39.0	11	4 x 6.5	1.00 x 36 x 4	13.5	26	18	17	480	Configure
RTSP39-11.0-7	39	11.0 x 5.5 x 39.0	7	4 x 6.5	1.25 x 42 x 6	15	47	36.5	28.4	720	Configure
RTSP39-14.0-7	39	14.0 x 8.5 x 39.0	7	4 x 6.5	1.50 x 54 x 6	20	101.8	80	63.5	1075	Configure
RTSP45-10.0-11	45	10.0 x 4.6 x 39.0 5.02 x 3.9 x 7.75	11	4 x 6.5	1.00 x 36 x 4	13.5	18.3	13.2	9.3	488	Configure
RTSP45-11.0-7	45	11.0 x 5.5 x 39.0 6.10 x 4.9 x 8.30	7	4 x 6.5	1.25 x 42 x 6	15	36.8	28.5	22	800	Configure
RTSP45-12.0-7	45	12.0 x 7.8 x 30.0 8.5 x 5.95 x 18.25	7	4 x 6.5	1.5 x 54 x 6	16	66	50	39	1008	Configure
RTSP45-12.5-3	45	12.5 x 8.3 x 30.0 9.0 x 6.6 x 17.4	3	4 x 6.5	1.50 x 54 x 6	16.5	70	54	41	1342	Configure
RTSP45-14.0-7	45	14.0 x 8.3 x 41.0 9.0 x 8.0 x 7.0	7	4 x 6.5	1.50 x 54 x 6	20	80	60	45	1272	Configure
RTSP45-14.0-3	45	14.0 x 8.3 x 41.0 9.0 x 8.0 x 7.0	3	4 x 6.5	1.75 x 84 x 6	20	113	87	68	1729	Configure
RTSP50-10.0-11	50	10.0 x 4.6 x 39.0 5.02 x 3.2 x 12.75	11	4 x 6.5	1.00 x 36 x 4	13.5	12.9	8.9	5.7	510	Configure
RTSP50-11.0-7	50	11.0 x 5.5 x 39.0 6.10 x 4.2 x 13.3	7	4 x 6.5	1.25 x 42 x 6	15	27.3	20.6	15.4	802	Configure
RTSP50-12.0-7	50	12.0 x 7.8 x 30.0 8.5 x 5.3 x 23.25	7	4 x 6.5	1.50 x 54 x 6	16	42.1	33.4	26.8	937	Configure
RTSP50-12.5-3	50	12.5 x 8.3 x 30.0 9.0 x 5.9 x 22.4	3	4 x 6.5	1.50 x 54 x 6	16.5	27.4	19	12.6	1331	Configure
RTSP50-14.0-7	50	14.0 x 8.3 x 41.0 9.0 x 7.3 x 12.0	7	4 x 6.5	1.50 x 54 x 6	20	64	47	34	1323	Configure
RTSP50-14.0-3	50	14.0 x 8.3 x 41.0 9.0 x 7.3 x 12.0	3	4 x 6.5	1.75 x 84 x 6	20	93	72	55	1807	Configure
RTSP55-12.0-7	55	12.0 x 7.8 x 30.0 8.5 x 4.6 x 28.25	7	4 x 6.5	1.50 x 54 x 6	16	21	19	13	970	Configure
RTSP55-12.5-3	55	12.5 x 8.3 x 30.0 9.00 x 5.2 x 27.4	3	4 x 6.5	1.50 x 54 x 6	16.5	27.4	19	12.6	1331	Configure
RTSP55-14.0-7	55	14.0 x 8.5 x 39.0 9.00 x 6.5 x 17.8	7	4 x 6.5	1.50 x 54 x 6	20	33.2	23.4	15.9	1254	Configure
RTSP55-14.0-3	55	14.0 x 8.3 x 41.0 9.00 x 6.7 x 16.7	3	4 x 6.5	1.75 x 84 x 6	20	50.4	37.5	27.6	1646	Configure
RTSP60-12.0-7	60	12.0 x 7.8 x 30.0 8.5 x 3.8 x 33.25	7	4 x 6.5	1.50 x 54 x 6	16	15.7	11.2	7.9	1011	Configure
RTSP60-12.5-3	60	12.5 x 8.3 x 30.0 9.00 x 4.5 x 32.4	3	4 x 6.5	1.50 x 54 x 6	16.5	21.9	14.4	8.8	1375	Configure
RTSP60-14.0-7	60	14.0 x 8.5 x 39.0 9.00 x 5.8 x 22.6	7	4 x 6.5	1.50 x 54 x 6	20	26.7	17.9	11.2	1299	Configure
RTSP60-14.0-3	60	14.0 x 8.3 x 41.0 9.00 x 6.0 x 21.7	3	4 x 6.5	1.75 x 84 x 6	20	41.8	30.3	21.5	1705	Configure
RTSP65-12.5-3	65	12.5 x 8.3 x 30.0 9.00 x 3.8 x 37.4	3	4 x 6.5	1.50 x 54 x 6	16.5	17.2	10.6	5.6	1413	Configure
RTSP65-14.0-7	65	14.0 x 8.5 x 39.0 9.00 x 5.1 x 27.6	7	4 x 6.5	1.50 x 54 x 6	20	21.1	13.3	7.3	1333	Configure
RTSP65-14.0-3	65	14.0 x 8.3 x 41.0 9.00 x 5.3 x 26.7	3	4 x 6.5	1.75 x 84 x 6	20	34.5	24.3	16.5	1757	Configure
RTSP70-14.0-7	70	14.0 x 8.5 x 39.0 9.00 x 4.4 x 32.6	7	4 x 6.5	1.50 x 54 x 6	20	15.6	8.9	3.7	1363	Configure
RTSP70-14.0-3	70	14.0 x 8.3 x 41.0 9.00 x 4.6 x 31.7	3	4 x 6.5	1.75 x 84 x 6	20	26.8	18.1	11.4	1803	Configure

FINISHES

<u>Standard</u>	<u>Galvanized</u>	<u>K-KLAD</u>	<u>K-KLAD Over Galvanizing</u>
BRZ Bronze	G Galvanized	K813 Bronze	KZ13 Bronze
BLK Black		K821 Black	KZ21 Black
GRY Gray		K841 Gray	KZ41 Gray
GRN Green		K891 Green	KZ91 Green
WHT White		K881 White	KZ81 White
P Primed		K845 Natural Aluminum	KZ45 Natural Aluminum
NA Natural Aluminum			

1 YEAR WARRANTY

5 YEAR WARRANTY

10 YEAR WARRANTY

MOUNTING DESIGNATIONS

Tenon Mount

- 2** 2 3/8" x 4" TENON
- 3** 2 7/8" x 4" TENON
- 3.5** 3 1/2" x 6" TENON

Drill Mount

- DM10** Drilled for 1 Luminaire
- DM2090** Drilled for 2 Luminaires @ 90°
- DM2180** Drilled for 2 Luminaires @ 180°

4 4" x 6" TENON

DM3090 Drilled for 3 Luminaires @ 90°

DM3120 Drilled for 3 Luminaires @ 120°

DM4090 Drilled for 4 Luminaires @ 90°

Open Mount

OT Open Top

OTC Open Top includes Pole Cap

Gain Mount

1GSS4 (1) CXA

2GSS4 (2) CXA's located on the Same Side

3GSS4 (3) CXA's located on the Same Side

4GSS4 (4) CXA's located on the Same Side

2GBB4 (2) CXA's located Back to Back

4GBB4 (4) CXA's located Back to Back

1GSS9 (1) CXASQ

2GSS9 (2) CXASQ's located on the Same Side

3GSS9 (3) CXASQ's located on the Same Side

4GSS9 (4) CXASQ's located on the Same Side

2GBB9 (2) CXASQ's located Back to Back

4GBB9 (4) CXASQ's located Back to Back

OPTIONS

There are numerous options that can be ordered. Please indicate these selections under the options column in the catalog number. Example: CPL-WPR2-BC-CS-SC.

Accessories

BC Base Cover

NC Nut Covers

CPL Threaded Coupling*

NPL Threaded Nipple*

WPRP Festoon Opening**

CS Climbing Steps

SC Safety Cable

LAB Less Anchor Bolt

VDI Vibration Damper Internal

Poles ordered with climbing steps will include provisions for safety cable mounting.

Poles ordered with safety cable will be provided with one safety device and belt per order unless otherwise requested.

Optional Handholes

58HH 5" x 8" Handhole*

410HH 4" x 10" Handhole*

Extra Handholes

XHH Extra Handhole*

Embedment Pole Options

E Embedded Pole

GS Ground Sleeve

CTE Coal Tar Epoxy

For Embedment Poles:

Recommended Mounting Height	Recommended Embedment Depth
Less than 20'	4'
20' - 33'	6'
34' - 39'	7'
40' - 60'	10'

Additional Simplex

1S 1 @ 0° *

2S 2 @ 180° *

3S 3 @ 90° *

4S 4 @ 90° *

Greater embedment depths are available upon request.

Embedment poles greater than 60' are not available.

* Please advise size, location, and orientation. (Handholes are restricted by size of pole shaft diameter)
** Located 24" above baseplate and same side as handhole. (No electrical included)

PACKAGING

Immediately after coating, the lighting standard including the baseplate shall be wrapped in heavy corrugation specially designed and sized to achieve maximum protection in transit.

KW Industries, Inc. coating process system and stringent quality control procedures provide our customer the finest quality lighting standards in the industry.

[Printer Friendly View](#)